Image not found or type unknown

06-11-2026

187989 ABBOT

5mm 26x30 cm./10.2x11.8in. • KM65

Información Técnica / Technical Information

Icon	Test	Standard	Result
Image not found or type unknown	SCRATCH HARDNESS	UNE EN 67-101	GLOSSY 4 MATT-5
	SLIP RESISTANCE	UNE-EN 16165 Anexo C	CLASE 0 / CLASS 0

Embalaje / Packing

m²		Kg	Lbs		m²	m²
12.82	23	18.4	40.57	54	1.79	96.88

Usos / Uses

✓	NO	✓	✓	NO	✓	NO	✓	✓	✓	NO

C = CONSULTAR / CONSULT

Characteristics

Image not found or type unknown Shade variation
Shade variation

Image not found or type unknown Satin finish
Satin finish

Image not found or type unknown Porcelain
Porcelain

Packaging icon

Pieza/m2
Piece/sqm

Piezas/caja
Pieces/box

Kg/caja
Kg/box

Libras/caja
Lbs/box

Cajas/pallet
Boxes/pallet

M2/caja
sqm/box

M2/pallet
Sqm/pallet

Icons of uses

Outdoor walls
Outdoor walls

Outdoor floors
Outdoor floors

Indoor walls
Indoor walls

Indoor floors
Indoor floors

Commercial flooring
Commercial flooring

Underfloor heating installation
Underfloor heating installation

Shower floor
Shower floor

Shower wall
Shower wall

Swimming pool. Wall and floor (depth>1,5m)
Swimming pool. Wall and floor (depth>1,5m)

Walls high vapor condensation areas
Walls high vapor condensation areas

Image not found or type unknown

Swimming pool (on steps and depth bottoms <1.5m, only C3 products)
Swimming pool (on steps and depth bottoms <1.5m, only C3 products)

ATTENTION

Carefully follow these instructions to ensure correct installation.

- Installation should be carried out by a qualified professional.
- Before installing ensure that the material is in perfect condition. Make sure you check the colours, finishes and thicknesses because DUNE will not accept any claims or returns of material after it has been installed.
- Before each stage, on one part test all of the materials and tools to be used and evaluate the final finish of the test. Should you fail to achieve the desired results do not continue with the installation, and consult our sales team.
- In public places materials must comply with the slipperiness requirements of the Spanish Technical Building Code.
- This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by DUNE CERÁMICA S.L.

Tabla de adhesivos / Adhesives Table

	Cemento cola C1 C1 concrete glue	Cemento cola C2 C2 concrete glue	Adhesivo epoxidico Epozi adhesive
KERAKOLL	ESPECIAL ECO	H 40 ECO FLEX	SUPERFLEX ECO
MAPEI	TIXOBOND	KERAFLEX MAXI S-1	KERALASTIC T

	Mortero adhesivo látex Latex adhesive mortar
LATICRETE	Mortar 211 + Laticrete 4237

Productos de tratamiento / Tratment products

	Código Code	Descripción Description	Código PHP recomendado Recommended retail price
CRISTAL GLASS	185463	ANTIGLISS	D787
PIEDRA STONE	184507	CERA LIQUIDA PROTECTORA LIQUID PROTECTIVE WAX	D945
	184508	SELLADOR ANTIMANCHAS STAIN-PROF SEALER	D969

Tabla de pastas de rejuntar / Grouting pastes table

	Pasta de rejuntar cementosa Cement grouting material	Pasta de rejuntar epoxi Epoxy grouting material
KERAKOLL	FUGABELLA ECO PORCELANA	FUGALITE
MAPEI	KERACOLOR FF	KERAPOXY
LATICRETE	LATICCRETE serie 1600	-