Image not found or type unknown

06-11-2026

E230879 METRO WHITE GLOSSY

8mm 7,5x15 cm./3x5.9in. • M782

Información Técnica / Technical Information

Icon	Test	Standard	Result
Image not found or type unknown	DIMENSIONS	UNE EN ISO 10545-2	± 0,5%
Image not found or type unknown	WATER ABSORPTION	UNE EN ISO 10545-3	E > 10%
Image not found or type unknown	CHEMICAL RESISTANCE	UNE EN ISO 10545-13	GA
Image not found or type unknown	FLATNESS	UNE EN ISO 10545-2	± 0,5%
Image not found or type unknown	CRAZING RESISTANCE	UNE EN ISO 10545-11	CUMPLE / ACCOMPLISH
Image not found or type unknown	RESISTANCE TO STAINS	UNE EN ISO 10545-14	5
Image not found or type unknown	BREAKING STRENGTH	UNE EN ISO 10545-4:9	>12 N/MM2
Image not found or type unknown	FROST RESISTANCE	UNE EN ISO 10545-12	NO CUMPLE
Image not found or type unknown	RESISTANCE TO THERMAL SHOCK	UNE EN ISO 10545-9	CUMPLE / ACCOMPLISH

Embalaje / Packing

m²		Kg	Lbs		m²	m²
88.89	90	12.6	27.78	75	1.01	75.94

Usos / Uses

NO	NO	✓	NO	NO	NO	NO	✓	NO	✓	NO

C = CONSULTAR / CONSULT

Characteristics

Shade variation
Shade variation

Gloss finish
Gloss finish

Irregular texture
Irregular texture

Packaging icon

Pieza/m2
Piece/sqm

Piezas/caja
Pieces/box

Kg/caja
Kg/box

Libras/caja
Lbs/box

Cajas/pallet
Boxes/pallet

M2/caja
sqm/box

M2/pallet
Sqm/pallet

Icons of uses

Outdoor walls
Outdoor walls

Outdoor floors
Outdoor floors

Indoor walls
Indoor walls

Indoor floors
Indoor floors

Commercial flooring
Commercial flooring

Underfloor heating installation
Underfloor heating installation

Shower floor
Shower floor

Shower wall
Shower wall

Swimming pool. Wall and floor (depth>1,5m)
Swimming pool. Wall and floor (depth>1,5m)

Walls high vapor condensation areas
Walls high vapor condensation areas

Swimming pool (on steps and depth bottoms <1,5m, only C3 products)
Swimming pool (on steps and depth bottoms <1.5m, only C3 products)

ATTENTION

Carefully follow these instructions to ensure correct installation.

- Installation should be carried out by a qualified professional.
- Before installing ensure that the material is in perfect condition. Make sure you check the colours, finishes and thicknesses because DUNE will not accept any claims or returns of material after it has been installed.
- Before each stage, on one part test all of the materials and tools to be used and evaluate the final finish of the test. Should you fail to achieve the desired results do not continue with the installation, and consult our sales team.
- In public places materials must comply with the slipperiness requirements of the Spanish Technical Building Code.
- This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by DUNE CERÁMICA S.L.

Tabla de adhesivos / Adhesives Table

	Cemento cola C1 C1 concrete glue	Cemento cola C2 C2 concrete glue	Adhesivo epoxidico Epozi adhesive
KERAKOLL	ESPECIAL ECO	H 40 ECO FLEX	SUPERFLEX ECO
MAPEI	TIXOBOND	KERAFLEX MAXI S-1	KERALASTIC T

	Mortero adhesivo látex Latex adhesive mortar

LATICRETE	Mortar 211 + Laticrete 4237

Productos de tratamiento / Tratment products

	Código Code	Descripción Description	Código PHP recomendado Recommended retail price
CRISTAL GLASS	185463	ANTIGLISS	D787
PIEDRA STONE	184507	CERA LIQUIDA PROTECTORA LIQUID PROTECTIVE WAX	D945
	184508	SELLADOR ANTIMANCHAS STAIN-PROF SEALER	D969

Tabla de pastas de rejuntar / Grouting pastes table

	Pasta de rejuntar cementosa Cement grouting material	Pasta de rejuntar epoxi Epoxy grouting material
KERAKOLL	FUGABELLA ECO PORCELANA	FUGALITE
MAPEI	KERACOLOR FF	KERAPOXY
LATICRETE	LATICCRETE serie 1600	-