



186544 THEA

8mm 30x30 cm./11.8x11.8in. • D689

Información Técnica / Technical Information

| Icon | Test | Standard | Result |
|------|------|----------|--------|
|------|------|----------|--------|

Embalaje / Packing

| | | | | | | |
|-------|----|-------|-------|----|------|-------|
| | | | | | | |
| 11.11 | 11 | 14.52 | 32.01 | 81 | 0.99 | 80.19 |

Usos / Uses

| | | | | | | | | | | | |
|----|----|---|----|----|----|----|---|----|----|----|----|
| | | | | | | | | | | | |
| NO | NO | ✓ | NO | NO | NO | NO | ✓ | NO | NO | NO | NO |

C = CONSULTAR / CONSULT

Characteristics

| | | | |
|--|---|--|-------------------------------------|
| | Shade variation Shade variation | | Satin finish Satin finish |
|--|---|--|-------------------------------------|

Packaging icon

| | | | | | | | |
|--|-------------------------------------|--|----------------------------------|--|--------------------------------|--|-------------------------------|
| | Pieza/m2 Piece/sqm | | Piezas/caja Pieces/box | | Kg/caja Kg/box | | Libras/caja Lbs/box |
| | Cajas/pallet Boxes/pallet | | M2/caja sqm/box | | M2/pallet Sqm/pallet | | |

Icons of uses

| | | | | | | | |
|--|--|--|---|--|---|--|---------------------------------------|
| | Outdoor walls Outdoor walls | | Outdoor floors Outdoor floors | | Indoor walls Indoor walls | | Indoor floors Indoor floors |
| | Commercial flooring Commercial flooring | | Underfloor heating installation Underfloor heating installation | | Shower floor Shower floor | | Shower wall Shower wall |
| | Swimming pool. Wall and floor (depth>1,5m) Swimming pool. Wall and floor (depth>1,5m) | | Walls high vapor condensation areas Walls high vapor condensation areas | | Swimming pool (on steps and depth bottoms<1.5m, only C3 products) Swimming pool (on steps and depth bottoms <1.5m, only C3 products) | | |

ATTENTION

Carefully follow these instructions to ensure correct installation.

- Installation should be carried out by a qualified professional.
- Before installing ensure that the material is in perfect condition. Make sure you check the colours, finishes and thicknesses because DUNE will not accept any claims or returns of material after it has been installed.
- Before each stage, on one part test all of the materials and tools to be used and evaluate the final finish of the test. Should you fail to achieve the desired results do not continue with the installation, and consult our sales team.
- In public places materials must comply with the slipperiness requirements of the Spanish Technical Building Code.
- This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by DUNE CERÁMICA S.L.

Tabla de adhesivos / Adhesives Table

| | Cemento cola C1 C1 concrete glue | Cemento cola C2 C2 concrete glue | Adhesivo epoxidico Epozi adhesive |
|-----------|---|-------------------------------------|--------------------------------------|
| KERAKOLL | ESPECIAL ECO | H 40 ECO FLEX | SUPERFLEX ECO |
| MAPEI | TIXOBOND | KERAFLEX MAXI S-1 | KERALASTIC T |
| | Mortero adhesivo látex Latex adhesive mortar | | |
| LATICRETE | Mortar 211 + Laticrete 4237 | | |

Productos de tratamiento / Tratment products

| | Código Code | Descripción Description | Código PHP recomendado Recommended retail price |
|------------------|----------------|--|--|
| CRISTAL GLASS | 185463 | ANTIGLISS | D787 |
| PIEDRA STONE | 184507 | CERA LIQUIDA PROTECTORA LIQUID PROTECTIVE WAX | D945 |
| | 184508 | SELLADOR ANTIMANCHAS STAIN-PROF SEALER | D969 |

Tabla de pastas de rejuntar / Grouting pastes table

| | Pasta de rejuntar cementosa Cement grouting material | Pasta de rejuntar epoxi Epoxy grouting material |
|------------------|--|---|
| KERAKOLL | FUGABELLA ECO PORCELANA | FUGALITE |
| MAPEI | KERACOLOR FF | KERAPOXY |
| LATICRETE | LATICRETE serie 1600 | - |